



P.O. Box 1789 • Amarillo, TX 79105 806-622-1273
 2401 Sundown Lane, 79118 Fax: 806-622-3258
 www.amarillogear.com E-mail: info@amarillogear.com

Amarillo "A" Series Fan Drives for Cooling Towers

**Optional Features - to be added to
list price of standard drives** NOTE 4

MODEL	LIST PRICE <small>NOTE 1</small>	OIL HEATER & THERMOSTAT	OIL LEVEL SWITCH <small>NOTE 2</small>	NON REVERSE	LOW SPEED OPTION (NET) <small>NOTE 3</small>	SYNTHETIC OIL (NET)	304SS BALL VALVE (NET)	EXPORT BOX (NET) <small>NOTE 5</small>
A20	3,970	NA	890	1,830	430	70	70	60
A22	5,680	NA	890	1,830	470	170	70	70
A27	10,970	CF	890	2,040	530	480	70	130
A32	20,610	550	890	2,440	NA	820	95	310
A34	28,390	860	890	2,440	NA	1,020	95	400
A36	33,640	860	890	2,440	NA	1,020	95	400
A38	36,850	860	890	2,440	NA	1,020	95	400

Prices of all Amarillo Drives are EXW, Amarillo, Texas

NA: Not Available
CF: Contact Factory

Notes:

- Prices are for standard rotation and standard ratios as listed in our current catalog. For special paint, special rotation, or special output shaft requirements, please contact the factory.
- Oil level switch is CSA listed for hazardous location: Class 1, Div. 1, Groups C & D. Switch is rated 10 amps @ 125 VAC. SPDT is standard. DPDT is available for an additional \$100 list.
- Low Speed Option is a proprietary modification to the single reduction gearbox that allows for no minimum" input (motor) speed when used in conjunction with Variable Frequency Drives (VFD). The minimum input (motor) speed without the Low Speed Option is 450 rpm. Input (motor) speed less than 450 rpm on double reduction gearboxes will require the Electric Oil Pump option.
- Optional equipment and features may add to delivery time.
- Export boxes are made with heat treated lumber.